



PLASTIC SYSTEMS INDUSTRIES

VINYLE WHITE 75 μ COLLE EXTRA FORTE

Face Material

Gloss white or clear polymeric soft vinyl.

Type	Polymeric vinyl	
Colour and Finish	Gloss white	
Weight	100 g/m ² \pm 10%	ISO-536
Thickness	75 μ \pm 10%	ISO 534-80

Adhesive

Permanent adhesive with excellent adhesion on low energy surfaces (i.e. PP or PE containers). The adhesive has a very high peel adhesion and medium cohesion.

Reference	ASP32	
Type	Permanent	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+100°C	
Shear	Medium	
Tack	13 N/25mm	FINAT FTM9
Final Adhesion	15 N/25mm	FINAT FTM2

Liner

Type	Siliconised two side PE Kraft	
Colour and Finish	White	
Weight	144 g/m ² \pm 10%	PP-032 - ISO 536
Thickness	155 μ \pm 10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Decorative applications for plastics fairing or tanks for motocross, quad bikes and Go Karts; Warning applications on heavy equipment and industrial trucks.

Printing Methods

Printable with UV and solvent screen-printing, UV offset and solvent and eco-solvent based ink-jet. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Plastic Systems Industries which has not undergone further processing, under the following **STORAGE CONDITIONS:**

- This material must be stored at a temperature of 22°C \pm 2°C and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.