

## BLOCKOUT ROUGH WALL STICKER-GLOSSY

- Code No.:** I-1308
- Description:** High quality rough wall sticker, glossy polymeric white soft PVC film with transparent adhesive. Offered with a liner of double-side PE-coated paper.
- Surface:** 90±5um polymeric white glossy PVC film.
- Adhesive:** 45±3um transparent adhesive-permanent.
- Liner:** 120±5gsm double-side PE-coated white kraft paper.
- Warranty:** 1 year after production.
- Compatible Ink:** UV Ink/ Eco Solvent Ink/ HP Latex Inks
- Features:** With polymeric white PVC film, I-1308 is more flexible which can be perfectly attached to the substrates with heat gun and it can completely cover the background color with clear adhesive.
- Applications:** Widely used for rough wall graphics.
- Size:** 1270/ 1370MM\*50M

### Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.090MM ± 0.005MM
Adhesive Thickness	ZC/QR08	0.045MM ± 0.003MM
Liner Thickness	ZC/QR08	0.130MM ± 0.010 MM
Surface brightness	ZC/QR08	60-85GS
	Tested by D60 standard Photometric apparatus;	
Adhesive Force	ZC/QR08	2.0± 18%kg/inch
Release Force	ZC/QR08	0.030± 0.005 kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.5
Test Temperature		25 ± 2°C, 65% ± 15%RH
Application Temperature		10°C-35°C 30%-70%RH
Storage Temperature		10°C-35°C 30%-70%RH

