

GRAPHICS - INK-JET DIGITAL

Issue date : 08/09/2010  
Date last modification : 12/04/2018**4-GL3B-05656 RI-JET 170 MAT WHITE AR802 REMOVABLE WK135 N****Face Material**

Mat white monomeric soft vinyl.

|                   |                           |            |  |
|-------------------|---------------------------|------------|--|
| Type              | Monomeric vinyl           |            |  |
| Colour and Finish | Mat white                 |            |  |
| Weight            | 210 g/m <sup>2</sup> ±10% | ISO-536    |  |
| Thickness         | 170 μ ±10%                | ISO 534-80 |  |

**Adhesive**

Removable adhesive offering easy and clean removability from glass and from many other substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

|                  |                            |  |  |
|------------------|----------------------------|--|--|
| Reference        | AR802 removable            |  |  |
| Type             | Acrylic removable          |  |  |
| Min. Appl. Temp. | +10°C                      |  |  |
| Service Temp.    | -20°C/+80°C                |  |  |
| Shear            | Medium                     |  |  |
| Tack             | Medium N/inch <sup>2</sup> |  |  |
| Final Adhesion   | Medium N/inch              |  |  |

**Liner**

|                   |  |                  |  |
|-------------------|--|------------------|--|
| Type              | One side siliconised clay coated Kraft |                  |  |
| Colour and Finish | White                                  |                  |  |
| Weight            | 135 g/m <sup>2</sup> ±10%              | PP-032 - ISO 536 |  |
| Thickness         | 145 μ ±10%                             | ISO 534          |  |
| Transparency      | n.a. %                                 | DIN 53 147-64    |  |

**Applications**

For advertising and promotional applications (outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis).

**Printing Methods**

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

