

## CANVAS EB 380 SM



- **Substrate:** 100% cotton textile with an irregular matte surface (canvas). It presents excellent quality of printing and stability. In addition to this it also reveals a bright color reproduction and fast drying.
- **Adhesive:** No adhesive
- **Durability:** ~ 5 years
- **Common uses:** Suitable for indoor applications such as art prints, posters, exhibition works and stage decoration.
- **Recommended printing method:** UV, solvent, Latex

### **PROPERTIES OF THE SUBSTRATE**

	<i>Average value</i>	<i>Standard used</i>
Grammage (g/m <sup>2</sup> )		
Thickness (µm)	380	
Temperature of use (°C)	20 – 30	
Relative Humidity (use) (%)	50	

### *CONSIDERATIONS AND RECOMMENDATIONS*

- o Surface for application: flat.
- o Film not recommended for outdoor applications, floor graphics (areas with car traffic), flexible or low energy films, painted or non-painted carton walls, plaster walls, wallpaper, poorly cleaned or rough surfaces, surfaces with degraded ink.
- o Do not expose to common spills or vapours.
- o Non-vertical application results in a significant decrease of the durability, as well as an inadequate climate and solar exposure. Before film usage, it is recommended that it is left at least 24h at the temperature of the workplace