



Slip-resistant Floor Sticker

-----Technical Data Sheet -----

- Code No.:** I-1277
- Description:** Premium quality PVC surface with coating of strong slip-resistance (R11 grade). Offered with a liner of double-side PE-coated paper.
- Surface:** 300±30um PVC surface with coating of strong slip-resistance(R11 grade).
- Adhesive:** 30±3um transparent adhesive-permanent.
- Liner:** 135±5gsm double-side PE-coated white wood-pulp paper.
- Durability:** Indoor use 3 months to 6months, depends on the environment.
- Compatible Ink:** Eco Solvent Ink/ HP Latex Inks
- Features:** With PVC surface, I-1277 could be printable for indoor short time advertising, The special coating surface makes I-1277 have strong slip-resistance.
- Applications:** Widely used for any indoor smooth and flat floor..
- Size Available:** 1270MM *30/50M

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness(with coating)	ZC/QR08	0.300MM-0.030MM
Adhesive Thickness	ZC/QR08	0.030MM ± 0.003MM
Liner Thickness	ZC/QR08	0.140MM ± 0.010MM
Surface brightness	ZC/QR08	/
Adhesive Force	ZC/QR08 20min on SS	1400~1600g/inch
Release Force	ZC/QR08	30±15g/inch
Initial Tack	20Minutes in the standard lab	Ball No.5-No.7
Test Temperature		25 ± 2°C, 65% ± 15% RH
Application Temperature		10°C-35°C 30%-70% RH
Storage Temperature		10°C-35°C 30%-70% RH

▲Important Notice:

The information and typical values shown are based on an ongoing process of research and development undertaken by BGS. The values listed herein are only reference value and shall not be used in investigation. The information herein are subject to change without prior notice and BGS shall not be liable for any such changes. This does not constitute a warranty or in any manner whatsoever.

Customers' improper usage may result in destruction and loss of materials. BGS cannot hold the liability for inaccurate or unauthorized representation made with respect to BGS products.

For further information, please visit our website www.BGS-Taiwan.com Or

Email to Info@BGS-Taiwan.com.

