



WHITE FLOOR STICKER-DOUBLE PE LINER

-----Technical Data Sheet -----

Code No.: I-1307
Description: Premium quality white sandblast matte PVC surface with a liner of single side PE-coated paper.
Surface: 200±10um white sandblast matte PVC film.
Adhesive: 30±3um transparent adhesive-permanent.
Liner: 120±5gsm double-side PE-coated white kraft paper.
Durability: Indoor use up to 1 year.

Compatible Ink: UV Ink/ Eco Solvent Ink/ HP Latex Inks

Features: With sandblast matte PVC, I-1307 has better slip resistance(R10 grade) than other glossy PVC floor sticker.

Applications: Widely used for floor graphics.

Size: 1.27 *30/50M

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.200MM ± 0.010MM
Adhesive Thickness	ZC/QR08	0.030MM ± 0.003MM
Liner Thickness	ZC/QR08	0.130MM ± 0.010 MM
Surface brightness	ZC/QR08	Approx. 4 GS
	Tested by D60 standard Photometric apparatus;	
Adhesive Force	ZC/QR08	1.1kg/inch± 18%
Release Force	ZC/QR08	Approx. 0.015kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.9
Test Temperature		25 ± 2°C, 65% ± 15%RH
Application Temperature		+10°C to +60°C
Storage Temperature		+25°C to +28°C

▲ Important Notice:

The information and typical values shown are based on an ongoing process of research and development undertaken by BGS. The values listed herein are only reference value and shall not be used in investigation. The information herein are subject to change without prior notice and BGS shall not be liable for any such changes. This does not constitute a warranty or in any manner whatsoever.

Customers' improper usage may result in destruction and loss of materials. BGS cannot hold the liability for inaccurate or unauthorized representation made with respect to BGS products.

For further information, please visit our website www.BGS-Taiwan.com Or

Email to Info@BGS-Taiwan.com.

