

## ULTRA CLEAR WINDOW STICKER

-----Technical Data Sheet -----

**Code No.:** SF 2903

**Description:** Premium quality high clear PVC film. Transparent glossy PVC film with transparent adhesive. Offered with a liner of matte PET release film.

**Surface:** 80±5um transparent glossy PVC film.

**Adhesive:** 25±3um transparent clear-removable.

**Liner:** 105±3um matte PET release film.

**Durability:** Outdoor use up to 1 year.

**Compatible Ink:** UV Ink/ Eco Solvent Ink/ HP Latex Inks.

**Features:** With high clear PVC film, SF 2903 has super clear effect after being printed with eco-solvent ink, HP Latex ink and UV ink, especially UV ink in color-white-color printing.

**Certifications :** SF 2903 has low inflammability certified M1 and have the RoSH certificate.

**Applications:** Widely used for storefront window graphics.

**Size:** 1.52\*50M

### Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.080MM ± 0.005MM
Adhesive Thickness	ZC/QR08	0.025MM ± 0.003MM
Liner Thickness	ZC/QR08	0.105MM ± 0.003MM
Surface brightness	ZC/QR08 Tested by D60 standard Photometric apparatus;	114.5±5GS
Adhesive Force	ZC/QR08	0.270kg/inch ± 18%
Release Force	ZC/QR08	Approx. 0.005kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.7
Test Temperature		25 ± 2°C, 65% ± 15%RH
Application Temperature		10°C-35°C 30%-70%RH
Storage Temperature		10°C-35°C 30%-70%RH